



VKCD-1329ASSM

Article number: 208589

1/3" Mini Dome, Fixed, clear, 3.6mm, 700TVL, 12VDC, Vandal resistant, Surface

Mainfeatures

1/3" colour board camera with Super HAD CCD

Resolution of 700 horizontal lines

Digital signal processing (DSP)

White-coloured aluminium die-cast casing

Easy indoor and outdoor installation (IP66)

Vandal resistant

Integrated lens F2.0/3.6mm

Automatic shutter control

Automatic white balance (ATW)

Clear Lexan bubble, 57mm

For wall and ceiling surface mounting

Specifications

Camera:

Sensor size	1/3"
Imager	CCD, Sony Super HAD II Interline Transfer
System	electronic Day&Night
Sensitivity	0,1 Lux, at F1.2, 50 IRE
Low speed shutter	no
Wide Dynamic Range (WDR)	no
Backlight compensation	BLC
Day/Night switching	auto
IR cut filter	OLPF (Overlay Low Pass Filter)
Signal-to-noise ratio	-50 db

Video:

VKCD-1329ASSM

Continued Specifications

Video standard	PAL
Horizontal resolution	700 TVL
Synchronization	internal
Lens:	
Lens type	fixed focal length
Focal length	3,6 mm
Digital zoom	no
MOD (Minimum object distance)	0,1 m
Horizontal angle of view	68 °
Active picture elements	976(H) x 582(V) pixels
Features:	
Motion detector	no
e-PTZ support	no
Digital Noise Reduction (DNR)	no
Interfaces / Inputs / Outputs:	
Video outputs	composite (CVBS), Composite (CVBS)
Alarm inputs	no
Alarm outputs	no
Serial interfaces	no
General:	
Dimensions (HxWxD)	60,5x80
Illumination	no
Colour (housing)	white
Colour (bubble)	clear
Housing	outdoor
Housing material	aluminium
Weight	170g
Heater	no
Bubble	57mm (2.25"), polycarbonate plastic
Power consumption	1.5W
Mounting	ceiling mount, wall mount
Protection rating	IP66
Supply voltage	12VDC
Temperature range (operation)	-10°C ~ +50°C
Vandalism resistant	yes
Scope of delivery:	
Parts supplied	manual, screw set
Notes:	

Special features

Optional mounting accessories needed

VKCD-1329ASSM

Available Accessories

Image	Prod. No / Label	Description
	217344 / MAM-5ME1001MTA	Multisignal Converter, HD-TVI , AHD, 960H to IP, H.264, 1920x1080, 12VDC
	218653 / PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug

Your Contact Person



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark
Deutschland
Tel.: +49 6074-888-333
E-Mail: info@eneo-security.com
Web: www.eneo-security.com