


Issue Date: January 18, 2013

INTRODUCING DELTA PMC 24V 150W WIDE RANGE POWER SUPPLY



- ▲ Universal AC input range
- ▲ Allow low input voltage from 85Vac to 264Vac without power de-rating
- ▲ Full Aluminum casing for light weight and corrosion resistant handling
- ▲ MTBF > 700,000 hours as per Telcordia
- ▲ Overvoltage / Overcurrent / Over Temperature Protections
- ▲ IP20 Terminal Block and Front Face Terminal Block options

Delta Electronics has added another 24V Panel Mount Power Supply series to the popular PMC series. Power Factor Correction (PFC) is designed into this model which operates at 24V output with 150W power rating at wide range input of 85Vac to 264Vac. Its active PFC of >0.99 @ 115Vac significantly improves the harmonic current levels to meet EN61000-3-2 standard and also reduces energy consumption. The lightweight and tough aluminum body weighs less than 540Grams and has a high efficiency of >89% with a typical MTBF of 700,000 hours which is one of the highest in the market. The product has several protection features including Overvoltage, Overcurrent and Over temperature.

Brand Comparison

	PMC-24V150W1BA	Chinese Brand	Japanese Brand
Output Voltage	24V	24V	24V
Input Voltage	85-264Vac	85-264Vac	85-264Vac
Efficiency	> 89.0%	> 83.0%	> 88.0%
Power Factor	> 0.99	> 0.98	> 0.99
Operating Temp.	-10°C to 70°C	-10°C to 60°C	-10°C to 71°C
Unit Weight	540g	760g	560g

PMC-24V150W1BA IS NOW AVAILABLE FOR SHIPMENT.

For more information and enquiries, please visit Delta standard power supplies homepage at www.DeltaPSU.com.

Upcoming Events

- **AHR Expo**
Location: Dallas, Texas, U.S.A.
Dates: 28 – 30 January 2013
- **India Automation Technology Fair**
Location: Mumbai, India
Dates: 1 – 3 February 2013

PMT PANEL MOUNT POWER SUPPLY



■ 24V 350W
PMT-24V350W1AG
(With UL mark only)

*Available for shipment

